MO.NO	Description	Part No	Part Noun Qual	Part Qty Issued	Tot Material Act	Act Tot Labor Cost	Actual Tot Cost
		2627	BOARD, FOXBORO (CCS)	0			
			CABLE, INSULATED, 600 V, FLAME RETARDANT,	0			
			#12 AWG, 3-CONDUCTOR,				
			XLPE/HYP,				
			90 DEG C MAX OPERATING				
			TEMPERATURE				
		D	Stainless steel rod, grade 347 H.	0			
		D	FABRICATE AND DELIVER: DUCT	0			
			WORK,				
			TO INCLUDE THE FOLLOWING:				
			36"/72" TURNING VANE SET,				
			30"/68" RECTANGULAR DUCT				
			SECTION,				
			30"/68" RECTANGULAR 90 DEG				
			ELBOW, 68"/30" SQUARE-TO-ROUND				
			TRANSITION,				
			46" ROUND 90 DEG ELBOW, 12"				
			THROAT, AND				
			END CAP, FLAT SHEET SIZED TO				
			EXISTING DUCT				
			**PER SKETCHES PERVIOUSLY SENT				
			BY BRET KENT**				
			WELD MATERIAL, ELECTRODE	10			
		D	TAPE MEASURE, 30' X 3/4", AUTO RETRACT,	0			
			STANLEY P/N 33-430				
			OIL, CUTTING	1			
		D	CABLE, POWER, INSULATED, 600	0			
			VOLT, FLAME RETARDANT, 4-CONDUCTOR,				
			12 AWG,				
			XLPE/HYPLON, 90 DEG C MAX				
			OPERATING TEMPERATURE				
		D	CABLE, INSTRUMENT,	0			
			SHIELDED-TWISTED, FLAME				
			RETARDANT, 600 VOLT, 16 AWG,				

IP7\_039433